










|  |   |
|--|---|
| <b>Part#</b>                             | 42532   |
| <b>Part Description</b>                  | 11 SMD LED Ultra Bright S.M.T. T10 Wedge LED Light Bulb |
| <b>Lamp Type</b>                         | 194   |
| <b>Lamp Base</b>                         | T10   |
| <b>Unit Wattage</b>                      | 0.87W   |
| <b>Voltage</b>                           | 14.5V   |
| <b>Frequency</b>                         | 60MA  |
| <b>Operating Temperature Environment</b> | (-)20Deg+80Deg  |
| <b>Operating Humidity</b>                | 5% to 95%   |
| <b>IP Class</b>                          |   |
| <b>Ventilation</b>                       | open air  |
| <b>Weight</b>                            | 2.5g  |
| <b>Size</b>                              | H:27mm;D:12mm   |
| <b>Package Type</b>                      | blister card  |
| <b>Number/ Carton</b>                    |   |
| <b>Carton Size</b>                       | 38x28x22cm  |
| <b>Certificates</b>                      | RoHS  |
| <b>Lense Type</b>                        |   |
| <b>Body Type</b>                         |   |
| <b>Work Environment</b>                  |   |
| <b>Luminous Efficacy</b>                 |   |
| <b>Lumen Maintenance</b>                 |   |
| <b>LED Life</b>                          | 50000hours  |
| <b>Warranty</b>                          | see website for more information                        |



# LEDLight.com



194 Wedge SMT 11 LED Light. 11 SMT LEDs. 3 forward firing and 8 side firing LEDs. Available colors for this product are super white, red, amber yellow, green and blue. Durable, shock and vibration proof, instant On/Off. Available in super white. .09 mA @ 13.8 VDC. 1.5 Watts@13.8 VDC. Approximate size is 1.15in x .44in.

| Color   | Beam Angle | Forward Lumen | Side Lumen | # of LEDs | # of chips per LED | LED Type | Kelvin     | Wave Length | Unit Amps | LED Watts | Unit Watts | CRI |
|---|------------|---------------|------------|-----------|--------------------|----------|------------|-------------|-----------|-----------|------------|-----|
| W      | 360 Deg    | 12 Lm         | 32 Lm      | 11        | 1                  | 11*1210  | 6000-7000k |             | 60MA      | 0.87W     |            |     |
| DW    |            |               |            |           |                    |          |            |             |           |           |            |     |
| WW   |            |               |            |           |                    |          |            |             |           |           |            |     |
| R    | 360 Deg    | 5 Lm          | 13 Lm      | 11        | 1                  | 11*1210  |            | 620-625nm   | 60MA      | 0.87W     |            |     |
| G    | 360 Deg    | 7 Lm          | 19 Lm      | 11        | 1                  | 11*1210  |            | 515-512nm   | 60MA      | 0.87W     |            |     |
| B    | 360 Deg    | 8 Lm          | 21 Lm      | 11        | 1                  | 11*1210  |            | 465-470nm   | 60MA      | 0.87W     |            |     |
| Y    | 360 Deg    | 4 Lm          | 11 Lm      | 12        | 1                  | 11*1210  |            | 465-470nm   | 60MA      | 0.87W     |            |     |
| UV   |            |               |            |           |                    |          |            |             |           |           |            |     |
| RGB  |            |               |            |           |                    |          |            |             |           |           |            |     |

LEDLight.com LLC

12215 East Chandler Heights Rd Chandler, AZ 85249

Toll Free 1(877)283-5060 Local 1(602)997-0366 Fax 1(602)861-4088