










<b>Part#</b>	47852
<b>Part Description</b>	T15 Wedge 36 Ultra Bright SMT LED
<b>Lamp Type</b>	194
<b>Lamp Base</b>	T10
<b>Unit Wattage</b>	2.1W
<b>Voltage</b>	14.5V
<b>Frequency</b>	150MA
<b>Operating Temperature</b>	(-)20Deg+80Deg
<b>Environment Temperature</b>	(-)20Deg+80Deg
<b>Operating Humidity</b>	5% to 95%
<b>IP Class</b>	
<b>Ventilation</b>	open air
<b>Weight</b>	3.8g
<b>Size</b>	H:48mm;D:15mm
<b>Package Type</b>	blister card
<b>Number/ Carton</b>	
<b>Carton Size</b>	38x28x22cm
<b>Certificates</b>	RoHS
<b>Lense Type</b>	
<b>Body Type</b>	
<b>Work Environment</b>	
<b>Luminous Efficacy</b>	
<b>Lumen Maintenance</b>	
<b>LED Life</b>	50000hours
<b>Warranty</b>	see website for more information



# LEDLight.com



36 LEDs, 6 forward firing and 30 side firing. Available in super white, red, yellow, green and blue. 12 VDC. 1.5 Watts Uses 50mA 10 Lumen Forward Firing 20 Lumen Side firing. Measures 1.50in from top to bottom and .58in in diameter. Great for malibu lighting.

Color	Beam Angle	Forward Lumen	Side Lumen	# of LEDs	# of chips per LED	LED Type	Kelvin	Wave Length	Unit Amps	LED Watts	Unit Watts	CRI
W 	360 Deg	24 Lm	120 Lm	36 led	1	36*1210	6000-7000K		150MA	0.058W	2.1W	
DW 												
WW 	360 Deg			36 led	1	36*1210			150MA	0.058W	2.1W	
R 	360 Deg	10 Lm	50 Lm	36 led	1	36*1210		620-625nm	150MA	0.058W	2.1W	
G 	360 Deg			36 led	1	36*1210		500-570nm	150MA	0.058W	2.1W	
B 	360 Deg			36 led	1	36*1210		420-470nm	150MA	0.058W	2.1W	
Y 	360 Deg	9 Lm	43 Lm	36 led	1	36*1210		465-470nm	150MA	0.058W	2.1W	
UV 												
RGB 												

LEDLight.com LLC

12215 East Chandler Heights Rd Chandler, AZ 85249

Toll Free 1(877)283-5060 Local 1(602)997-0366 Fax 1(602)861-4088