Part#	49587					
Part	12in flexible					
Description	1210 SMT 12V					
Lamp Type	LED strip					
Lamp Base						
Unit Wattage	0.96W					
Voltage	12V					
Frequency	50~60HZ					
Operating Temperature	lower than 60Deg					
Environment	-20 to 60Deg					
<u>Temperature</u> Operating Humidity	5% to 95%					
IP Class	IP55					
Ventilation	open air					
Weight	.05 lbs					
Size	12 in x .39 in					
Package	ledlight.com's					
Туре	box					
Number/	165/Ctn					
Carton	105/011					
Carton Size	5.92in x 5.14in					
Certificates	CE & RoHS					
Lense Type	no lens					
Body Type	flexible/protective rubber sleeve					
Work Environment	indoor/outdoor					
Environment Luminous Efficacy	85%					
Lumen Maintenance	5% per 20,000 hrs					
LED Life	20000hrs					
Warranty	see website for more information					



Flexible LED Light has two sided tape so just remove and stick into place. The LEDs are spaced at 1 per inch. CE and Rohs certified. Each color has a different Lumen output, watt consumption, and current consumption. Available in white, warm white, red, green, blue, yellow/amber. You can use the flexible LED Lights with a standard 9 volt transistor battery. Very low power consumption. Up to 24 feet of light can be illuminated with one 2A power supply. The flexible strips can be interconnected together using the connector. Very low profile. The flexible strip may also be cut down to size. There are cut marks that show where the flexible strip down to size. Please note after cutting the flexible strip it is not returnable for credit. You can calculate how many flexible strips footage you can run by a power supply by dividing the power supply wattage by the wattage per foot that the flexible led light uses. Great for outdoor/indoor parties, holidays, stage and other decorations, accent lighting, land-scaping, special events, etc.

Color	Beam Angle	Forward Lumen	-	# of LEDs	# of chips per LED	LED Type	Kelvin	Wave Length	Unit Amps	LED Watts	Unit Watts	CRI
w 🗌	120D	72L	0	12PCS			6000- 6500K		0.08A	0.08W	0.96W	75%
DW 📃												
ww	120D	48L	0	12PCS	1Chip		3000K		0.08A	0.08W	0.96W	75%
R	120D		0	12PCS	1Chip			630- 780nm	0.08A	0.08W	0.96W	75%
G	120D		0	12PCS	1Chip			500- 570nm	0.08A	0.08W	0.96W	75%
в	120D		0	12PCS	1Chip			420- 470nm	0.08A	0.08W	0.96W	75%
Υ 📒	120D		0	12PCS	1Chip			570- 600nm	0.08A	0.08W	0.96W	75%
UV												
RGB												

LEDLight.com LLC 12215 East Chandler Heights Rd Chandler, AZ 85249 Toll Free 1(877)283-5060 Local 1(602)997-0366 Fax 1(602)861-4088