










| | |
|--------------------------------|-----------------------------------|
| Part# | 64985 |
| Part Description | 25 Ultra Bright S25 SMT LED Light |
| Lamp Type | 1156, 1157 |
| Lamp Base | BA15S |
| Unit Wattage | 2.9W |
| Voltage | 14.5V |
| Frequency | 200MA |
| Operating Temperature | (-)20Deg+80Deg |
| Environment Temperature | (-)20Deg+80Deg |
| Operating Humidity | 5% to 95% |
| IP Class | |
| Ventilation | open air |
| Weight | 16g |
| Size | 38MM*38MM |
| Package Type | blister card |
| Number/ Carton | |
| Carton Size | 38x28x22cm |
| Certificates | RoHS |
| Lense Type | |
| Body Type | |
| Work Environment | |
| Luminous Efficacy | |
| Lumen Maintenance | |
| LED Life | 50000hours |
| Warranty | see website for more information |



LEDLight.com



25 Forward firing LEDs. Durable. Dimensions are, The square is 37.4mm square Roughly 6.5mm thick. The wire length is 60.0mm in length. And the base length is 21.6mm and diameter 15mm. Shock and Vibration proof. Instant on/off. monochromatic (pure) color. low heat. virtually unbreakable. 12 VDC. Uses 180 mA. Equivalent to 430 lumen output. Available in Super White, Red and Amber Yellow. 1156 replaces BA15S T25 T-25 1073 1093 1129 1141 1159 1259 1295 1383 1459 1619 1651 1680 2056 3496 5007 5008 7008 7506 7806 7527 1156 1759 3497 1156-18W 67 89 97 1156 12821 P21W LOW 61 63 67 #67 69 71 81 89 97 98 303 623 1003 1155 1247 1251 3497 5007 5008 12821 P21W. 1157 replaces BAY15D 2057 2357 2397 7528 3496.

| Color | Beam Angle | Forward Lumen | Side Lumen | # of LEDs | # of chips per LED | LED Type | Kelvin | Wave Length | Unit Amps | LED Watts | Unit Watts | CRI |
|---|------------|---------------|------------|-----------|--------------------|----------|------------|-------------|-----------|-----------|------------|-----|
| W  | 120 Deg | 230 Lm | 0 | 25 led | 2 | 25*5060 | 6000-7000K | | 200MA | 0.12W | 2.9W | |
| DW  | | | | | | | | | | | | |
| WW  | | | | | | | | | | | | |
| R  | 120 Deg | 47 Lm | 0 | 25 led | 2 | 25*5060 | | 620-625nm | 200MA | 0.12W | 2.9W | |
| G  | | | | | | | | | | | | |
| B  | | | | | | | | | | | | |
| Y  | 120 Deg | 80 Lm | 0 | 25 led | 2 | 25*5060 | | 465-470nm | 200MA | 0.12W | 2.9W | |
| UV  | | | | | | | | | | | | |
| RGB  | | | | | | | | | | | | |

LEDLight.com LLC

12215 East Chandler Heights Rd Chandler, AZ 85249

Toll Free 1(877)283-5060 Local 1(602)997-0366 Fax 1(602)861-4088