Photo of object

Function of controller pannel

ON/OFF button，it can open or close led anytime,when led is on the station of closing,The LCD will display “IC NUMBER: ***”,“***”is the value of current setting.

Play/pause button,when you want to see the static effection of led ,you may press this button to pause.

Adding button,to add the IC NUMBER,the most number is 255 (510 group of RGB)

Reducing button,to reduce the IC NUMBER,the least number is 16 (32 group of RGB)

Program chosing button,up direction，there are 83 programs in all.

Program chosing button,down direction.

Speed slow button,there are 100 step in all,the most number is 100

Speed quick button,the least number is 1

Function of remote pannel

ON/OFF: ON/OFF button，it can open or close led anytime,when led is on the station of closing,The LCD will display “IC NUMBER: ***”,“***”is the value of current setting.

MODE: Play/pause button,when you want to see the static effection of led ,you may press this button to pause.

S+: Speed quick button,the least number is 1
S-: Speed slow button,there are 100 step in all,the most number is 100

B+: Program chosing button,up direction，there are 83 programs in all.

B-: Program chosing button,down direction.

OUTPUT1&OUTPUT2 Description: L, K ,D, S is the corresponding signal of HL1606,which is L_I,CK_I,D_I,S_I.

PROGRAM Description:（Condiction：A1—Blue LED；A2—Red LED；A3—Green LED）

LEDLight.com LLC
12215 East Chandler Heights Rd Chandler, AZ 85249
Toll Free 1(877)283-5060 Local 1(602)997-0366 Fax 1(602)861-4088