

<b>Product</b>	<b>27 5050 Ultra Bright S25 SMD LED Light</b>
----------------	---



6 forward firing Ultra Bright SMT LEDs and 21 side firing Ultra Bright SMT LEDs. Durable, shock and vibration proof, instant On/Off. Monochromatic (pure) color, low heat generation, virtually unbreakable. 1156 single contact is used for turn signals. 1157 dual contact is used for tail light/ brake light. 1156 single contact is used for turn signals. 1157 dual contact is used for tail light/ brake light.

<b>Lens type</b>	None
<b>Body Type</b>	Circuit Board
<b>Work Environment</b>	Indoor
<b>Efficacy</b>	32 lm/ watt
<b>Lumen Maintenance</b>	30% decay @ 30,000 hrs
<b>Led Life</b>	25,000 and up
<b>Operating Humidity</b>	25%~85% RH
<b>Operating Temp</b>	100°F@70°F Room temp
<b>Operating Environment</b>	-4°F~104°F

<b>Lamp Type</b>	Turn/ Tail and Brake
<b>Lamp Base</b>	1156, 1157
<b>Unit Watts</b>	3 watts
<b>Operating Voltage</b>	12 Volt DC
<b>Frequency</b>	50Hz/60Hz
<b>IP Class</b>	20
<b>Ventilation</b>	Air
<b>Size</b>	1.93 in x .80 in

UL	ETL	CE	FCC	RoHs
NO	NO	YES	NO	YES

Color	Kelvin	Lumen	# of LEDs	# of Chips per LED	LED Type	Angle	LED Watts	CRI
23123W	5000k	97	27	1	SMD	360	.8	75
23123R	620nm	85	27	1	SMD	360	.8	75
23123Y	580nm	70	27	1	SMD	360	.8	75