Part Description PAR Light Lamp Type PAR Light Lamp Base E27 Unit Wattage 90-240V Frequency 50-60 Operating Temperature Phumidity IP Class Ventilation Weight 0.25kg/pcs Size 95mm*88mm Package Type Number/ Carton Size 540*467*318mm Certificates CE,RoHS Lense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life 50,000 hours Warranty 1 year		
Description Lamp Type PAR Light Lamp Base Poly Early Par Light Lamp Base E27 Unit Wattage Voltage Poly Early Frequency Foliage Foli	Part#	89785
Lamp Type Lamp Base Lamp Base E27 Unit Wattage Voltage 90-240V Frequency 50-60 Operating Temperature Environment Temperature Operating Humidity IP Class Ventilation Weight 0.25kg/pcs Size 95mm*88mm Package Type Number/ Carton Carton Size Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life PAR Light E27 AR Light A Carton Coverable 1 1 1 1 1 1 1 1 1 1 1 1 1		PAR30-8W
Unit Wattage Voltage 90-240V Frequency 50-60 Operating Temperature Environment Temperature Operating Humidity IP Class Ventilation Weight 0.25kg/pcs Size 95mm*88mm Package Type Number/ Carton Carton Size Certificates CE,RoHS Lense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life 50,000 hours	· ·	PAR Light
Wattage Voltage 90-240V Frequency Operating Temperature Environment Temperature Operating Humidity IP Class Ventilation Weight 0.25kg/pcs Size 95mm*88mm Package Type Number/ Carton Carton Size Certificates CE,RoHS Lense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life 50,000 hours	Lamp Base	E27
Frequency Operating Temperature Environment Temperature Operating Humidity IP Class Ventilation Weight Ocarton Carton Carton Carton Size Certificates Lense Type Work Environment Luminous Efficacy Lumen Maintenance LED Life Soom temperature room temperature starting		1
Operating Temperature Environment Temperature Operating Humidity IP Class Ventilation Weight Ocarton Carton Size Certificates Certifica	Voltage	90-240V
Temperature Environment Temperature Operating Humidity IP Class Ventilation Weight O.25kg/pcs Size 95mm*88mm Package Type Number/ Carton Carton Size Certificates Certificates Lense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life Voom temperature room temperature and use of the part o		50-60
Environment Temperature Operating Humidity IP Class Ventilation Weight O.25kg/pcs Size 95mm*88mm Package Type Number/ Carton Carton Carton Size Certificates Certificates Lense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life Noom temperature room temperature 280 427 LED Life So,000 hours		-20-40
Humidity IP Class Ventilation Weight 0.25kg/pcs Size 95mm*88mm Package Type Number/ Carton Carton Size 60boxes/Carton Carton Size 540*467*318mm Certificates CE,RoHS Lense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life 50,000 hours	Environment	room temperature
Ventilation Weight 0.25kg/pcs Size 95mm*88mm Package Type 60boxes/Carton Carton Size 540*467*318mm Certificates CE,RoHS Lense Type Body Type Work Environment Luminous Efficacy Lumen 280 427 LED Life 50,000 hours		
Weight 0.25kg/pcs Size 95mm*88mm Package Type 60boxes/Carton Carton Size 540*467*318mm Certificates CE,RoHS Lense Type Body Type Work Environment Luminous Efficacy Lumen 280 Maintenance 427 LED Life 50,000 hours	_	
Size 95mm*88mm Package Type Number/ Carton Carton 540*467*318mm Certificates CE,RoHS Lense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life 50,000 hours	Ventilation	
Package Type Number/ Carton Carton Size Certificates Certificates Cense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life CTNS 60boxes/Carton 60	Weight	0.25kg/pcs
Type Number/ Carton Carton Size Certificates Certificates Cense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life Coboxes/Carton Carton Carton Size CE,RoHS indoor Sa-54LM/W 280 427 50,000 hours	Size	95mm*88mm
Carton Carton Size 540*467*318mm Certificates CE,RoHS Lense Type Body Type Work Environment Luminous Efficacy Lumen 280 Maintenance 427 LED Life 50,000 hours	_	CTNS
Certificates Lense Type Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life CE,RoHS indoor 38-54LM/W 280 427 50,000 hours		60boxes/Carton
Lense Type Work Environment Luminous Efficacy Lumen Maintenance LED Life So,000 hours	Carton Size	540*467*318mm
Body Type Work Environment Luminous Efficacy Lumen Maintenance LED Life Work indoor 38-54LM/W 280 427 50,000 hours	Certificates	CE,RoHS
Work Environment Luminous Efficacy Lumen Maintenance LED Life indoor 38-54LM/W 280 427 50,000 hours	Lense Type	
Environment indoor Luminous Efficacy 38-54LM/W Lumen 280 Maintenance 427 LED Life 50,000 hours		
Luminous 38-54LM/W Efficacy 280 Lumen 427 LED Life 50,000 hours	Environment	indoor
Lumen 280 Maintenance 427 LED Life 50,000 hours	Luminous	38-54LM/W
LED Life 50,000 hours	Lumen	
Warranty 1 year		
	Warranty	1 year





8 Watt PAR30 Nichia LEDs

8 Watt PAR30 Nichia LEDs. 85-260 VAC. E27 Base. 50-60 Hz. Available in white and warm white. Very focused and well designed LED Lamp by Nichia. Nichia is the inventor of the white L.E.D. and has many patents. This LED measures from top to bottom 3.70in and a diameter of 3.73in.

Color	Beam Angle	Forward Lumen	# of LEDs	# of chips per LED	LED Type	Kelvin	Wave Length	Amps	LED Watts	Unit Watts	CRI
w 🗌	30/45	427	7		chia 083E	BT 5200K			8		70
DW											
ww	30/45	280	7	Ni	chia 083E	3000k			8		75
R											
G											
В											
Υ											
UV											
RGB											

LEDLight.com LLC

12215 East Chandler Heights Rd Chandler, AZ 85249 Toll Free 1(877)283-5060 Local 1(602)997-0366 Fax 1(602)861-4088