




# LEDLight.com

## Flexible 24 Inch Red/Green/Blue SMT 1210 LED Light Common Anode



Flexible LED Light has two sided tape so just remove and stick into place. The LEDs are spaced at 1 per inch. White at 12" is 30 Lumens, 24" 40 Lumens, 48" 47 Lumens. Each color has a different Lumen output, watt consumption, and current consumption. Available in white 6000 Kelvin, warm white 3000 Kelvin, red (630nm-780nm), green (500nm-570nm), blue (420-470), yellow/amber (570-600), and RGB. Using a RGB controller, you can have sync color changing. Each 12" length uses 80mA of current at 12 VDC.

Color	Beam Angle	Forward Lumen	Side Lumen	# of LEDs	# of chips per LED	LED Type	Kelvin	Wave Length	Amps	LED Watts	Unit Watts	CRI
W <input type="checkbox"/>				24								
DW <input type="checkbox"/>												
WW <input type="checkbox"/>				24								
R <input type="checkbox"/>				24								
G <input type="checkbox"/>				24								
B <input type="checkbox"/>				24								
Y <input type="checkbox"/>				24								
UV <input type="checkbox"/>												
RGB <input type="checkbox"/>	160					SMD1206						

Part#	94567
Part Description	Flexible LED Light
Lamp Type	LED strips
Lamp Base	
Unit Wattage	
Voltage	12V
Frequency	50-60Hz
Operating Temperature	-20°C -60°C
Environment Temperature	-20°C -40°C
Operating Humidity	0-95% non-condensing
IP Class	IP65
Ventilation	
Weight	
Size	24 inch
Package Type	white box
Number/ Carton	
Carton Size	
Certificates	CE ROHS
Lense Type	
Body Type	
Work Environment	
Luminous Efficacy	
Lumen Maintenance	
LED Life	10,000 hours
Warranty	1 year