

| | |
|----------------|--|
| Product | 27 Ultra Bright T25 Wedge SMT LED Light |
|----------------|--|



3136 3157 Wedge 27 Ultra Bright SMT LED Light 6 forward firing Ultra Bright SMT LEDs and 21 side firing Ultra Bright SMT LEDs. Durable, shock and vibration proof, instant On/Off. Monochromatic (pure) color, low heat generation, virtually unbreakable.

| | |
|-----------------------|------------------------|
| Lens type | None |
| Body Type | Plastic |
| Work Environment | Indoor/ Car lens |
| Efficacy | 32 lm/ watt |
| Lumen Maintenance | 30% decay @ 30,000 hrs |
| Led Life | 25,000 and up |
| Operating Humidity | 25%~85% RH |
| Operating Temp | 100°F@70°F Room temp |
| Operating Environment | -4°F~104°F |

| | |
|-------------------|---------------------|
| Lamp Type | Turn/Tail and Brake |
| Lamp Base | 3156/3157 |
| Unit Watts | 3 Watt |
| Operating Voltage | 12 Volt DC |
| Frequency | 50Hz/60Hz |
| IP Class | 20 |
| Ventilation | Air |
| Size | 2.10 x .78 in |

| UL | ETL | CE | FCC | RoHs |
|----|-----|-----|-----|------|
| NO | NO | YES | NO | YES |

| Color | Kelvin | Lumen | # of LEDs | # of Chips per LED | LED Type | Angle | LED Watts | CRI |
|--------|--------|-------|-----------|--------------------|----------|-------|-----------|-----|
| 23345W | 5000k | 97 | 27 | 1 | SMT | 360 | .8 | 75 |
| 23345R | 620nm | 85 | 27 | 1 | SMT | 360 | .8 | 75 |
| 23345Y | 580nm | 70 | 27 | 1 | SMT | 360 | .8 | 70 |