

<b>Product</b>	<b>43532 MR11 21 LED Light Low voltage 12 Volt AC/DC</b>
----------------	--



100 Lumen output. Comparable to a 10W Halogen. 1 Watt power consumption. 70 mA current consumption. Available in white 6500 Kelvin and warm white 3000 Kelvin. Long life of 30,000 hours. 50 Degree viewing angle. GX4.0 base. Operating voltage 12V AC or 12V DC. 1.36 inches diameter x 1.32 inches height. No ultraviolet (UVA, UVB, UVB) or radiofrequency (RF) energy. Can be dimmed with a variable AC or DC voltage supply. One per package.

<b>Lens type</b>	None
<b>Body Type</b>	Glass
<b>Work Environment</b>	Indoor
<b>Efficacy</b>	100Lm/Watts
<b>Lumen Maintenance</b>	30% Decay @ 30,000Hr
<b>Led Life</b>	Up To 50,000 Hr
<b>Operating Humidity</b>	25%~85% RH
<b>Operating Temp</b>	100°F@70°F Room temp
<b>Operating Environment</b>	-4°F~104°F

<b>Lamp Type</b>	MR11
<b>Lamp Base</b>	Bi-pin
<b>Unit Watts</b>	1
<b>Operating Voltage</b>	12V/DC
<b>Frequency</b>	50Hz/60Hz
<b>IP Class</b>	41
<b>Ventilation</b>	Air
<b>Size</b>	1.4in x 1.3in

UL	ETL	CE	FCC	RoHs
No	No	No	No	Yes

Color	Kelvin	Lumen	# of LEDs	# of Chips per LED	LED Type	Angle	LED Watts	CRI
43532W	6000k	100	21	1	DIP	50°	.01	80
43532WW	3000k	99	21	1	DIP	50°	.01	80