

| | |
|-----------------------------------|----------------------------------|
| Part# | 48465 |
| Part Description | 12 SMD Tower T10 Wedge |
| Lamp Type | T10 LED Lamp |
| Lamp Base | T10 |
| Unit Wattage | 2.88W |
| Voltage | 12V |
| Frequency | 50~60HZ |
| Operating Temperature Environment | lower than 60Deg |
| Operating Temperature Humidity | -20 to 60Deg |
| Operating Humidity | 5% to 95% |
| IP Class | IP44 |
| Ventilation | open air |
| Weight | 2.5kgs |
| Size | .40 in x 2.20 in |
| Package Type | LEDlight.com's card and blisters |
| Number/ Carton | 500pcs/Ctn |
| Carton Size | |
| Certificates | CE & RoHS |
| Lense Type | no lens |
| Body Type | copper |
| Work Environment | indoor |
| Luminous Efficacy | 100% |
| Lumen Maintenance | |
| LED Life | 10000hrs |
| Warranty | see website for more information |

LEDLight.com



194 Wedge 12 SMT LED Light. 120 Lumen output. Available in super white, red, yellow, green and blue. 240 mA @ 12 VDC. Size is 2.27 inches tip to bottom and the diameter is 0.51 inches. High tech heat sink to make the LED Light last longer. Replaces 194 T10 T-10 147 152 158 159 161 168 184 192 193 194 #194 259 280 285 447 464 555 558 585 655 656 657 1250 1251 1252 2450 2652 2921 2825 12256 12961 2521 2525 W5W.

| Color | Beam Angle | Forward Lumen | Side Lumen | # of LEDs | # of chips per LED | LED Type | Kelvin | Wave Length | Unit Amps | LED Watts | Unit Watts | CRI |
|-------|------------|---------------|------------|-----------|--------------------|----------|------------|-------------|-----------|-----------|------------|-----|
| W | 360 | 180L | 0 | 12 | 3 chips | 5050 | 6000-6500K | | 0.24A | 0.24W | 2.88W | 75% |
| DW | | | | | | | | | | | | |
| WW | 360 | 145L | 0 | 12 | 3 chips | 5050 | 3000-3500K | | 0.24A | 0.24W | 2.88W | 75% |
| R | 360 | | 0 | 12 | 3 chips | 5050 | | 630-780nm | 0.24A | 0.24W | 2.88W | 75% |
| G | 360 | | 0 | 12 | 3 chips | 5050 | | 500-570nm | 0.24A | 0.24W | 2.88W | 75% |
| B | 360 | | 0 | 12 | 3 chips | 5050 | | 420-470nm | 0.24A | 0.24W | 2.88W | 75% |
| Y | 360 | | 0 | 12 | 3 chips | 5050 | | 570-600nm | 0.24A | 0.24W | 2.88W | 75% |
| UV | | | | | | | | | | | | |
| RGB | | | | | | | | | | | | |

LEDLight.com LLC
12215 East Chandler Heights Rd Chandler, AZ 85249
Toll Free 1(877)283-5060 Local 1(602)997-0366 Fax 1(602)861-4088