

Product	56329 Festoon Super Flux 2 LED Light 1 3/4 Inches / 42 mm
----------------	--



Festoon Super Flux 2 LED Light. 2 forward firing super flux LED chips. 42mm or 1 5/8 Inches. Available in super white, red, yellow and blue. 2 Super Flux LEDs consume .040 Amps of current 40mA@12 VDC .552 Watt consumption. Please select 1 3/4 Inches for the replacement bulb number 560 569 578 211 212 212-2 2122 214-2 2142 6413 6429 DE3021 DE3022 DE3175 DE3425 DE4410 12844.

Lens type	None
Body Type	Aluminum
Work Environment	Indoor
Efficacy	200Lm/.55 Watts
Lumen Maintenance	30% Decay @ 30,000Hr
Led Life	Up To 50,000 Hr
Operating Humidity	25%~85% RH
Operating Temp	100°F@70°F Room temp
Operating Environment	-4°F~104°F

Lamp Type	Festoon
Lamp Base	Festoon
Unit Watts	.55
Operating Voltage	12V/DC
Frequency	50Hz/60Hz
IP Class	41
Ventilation	Air
Size	1.75in x .33in

UL	ETL	CE	FCC	RoHs
No	No	No	No	Yes

Color	Kelvin	Lumen	# of LEDs	# of Chips per LED	LED Type	Angle	LED Watts	CRI
56329W	6000k	200	2	3	DIP	180°	.02	80
56329R	620nm	190	2	3	DIP	180°	.02	80
56239B	520nm	190	2	3	DIP	180°	.02	80
56239Y	570nm	160	2	3	DIP	180°	.02	80